

# RUNDSLING



Art.	Size	Webbing width (mm)	Colour coded acc. to EN 1492-1	Working load limit with 1 round sling						Working load limit with 1 round sling				
				Straight lift	Choked lift	β				Straight lift up to 45°	Choked lift up to 45°	Straight lift 45°-60°	Choked lift 45°-60°	
						0°-7°	7°-45°	45°-60°	Up to 45°					45°-60°
				1.0	0.8	2.0	1.4	1.0	0.7	0.5	1.4	1.12	1.0	0.8
55.1000-2m	1m / 2m	30	WLL 1T	1.000	0.800	2.000	1.400	1.000	700	500	1.400	1.120	1.000	0.800
55.1000-4m	2m / 4m													
55.1000-6m	3m / 6m													
55.2000-2m	1m / 2m	60	WLL 2T	2.000	1.600	4.000	2.800	2.000	1.400	1.000	2.800	2.240	2.000	1.600
55.2000-4m	2m / 4m													
55.2000-6m	3m / 6m													
55.3000-2m	1m / 2m	90	WLL 3T	3.000	2.400	6.000	4.200	3.000	2.100	1.500	4.200	3.360	3.000	2.400
55.3000-4m	2m / 4m													
55.3000-6m	3m / 6m													
55.3000-8m	4m / 8m													
55.3000-10m	5m / 10m													
55.5000-4m	2m / 4m	150	WLL 5T	5.000	4.000	10.000	7.000	5.000	3.500	2.500	7.000	5.600	5.000	4.000
55.5000-6m	3m / 6m													
55.5000-8m	4m / 8m													
55.5000-10m	5m / 10m													
55.8000-4m	2m / 4m	240	WLL 8T	8.000	6.400	16.000	11.200	8.000	5.600	3.500	11.200	8.960	8.000	6.400
55.8000-8m	4m / 8m													



EN1492-2+A1:2008

Safety factor 7:1

Ved større mængder - ring og få specialpris